

Max 430

The Max 430 allows up to four users to simultaneously place low-cost calls to phones, fax machines and Net2Phone products all over the world.

The Max 430 provides:

- A versatile solution that enables both on-site and off-site users to make low-cost calls
- A combination of FXO and FXS ports, allowing you to connect regular telephones, fax machines, phone lines and/or a PBX system to make calls using Voice over Internet Protocol (VoIP)
- Easy integration with an existing network and phone system

Small Business & Internet Café Solution

Up to four simultaneous calls can be made through the Max 430, making it the perfect solution for small businesses and Internet Cafés. And with the Max 430, you are not limited to making calls from the physical location of the unit. The FXO line can be dedicated to off-premise calling, allowing you to dial into the Max and make low-cost calls from any phone, anywhere. In this way, corporations can save money by allowing employees to make calls through the Max when they are traveling for business. Internet Cafés can increase their revenue by enabling users to access their calling services from any location.

Flexible Connectivity Options

The Max 430 features one FXO and three FXS ports. With this configuration, you have a variety of connectivity options:

Port Type	Number	Connects To
FXS	3	<ul style="list-style-type: none">• Regular telephones, fax machines AND/OR• Analog trunk card of a PBX
FXO	1	<ul style="list-style-type: none">• Telephone line OR• Analog line card of a PBX

Easily Integrated with your Current Systems

The Max 430 can be easily added to existing network and phone systems to route calls over the Internet. Simply connect the Max to a switch or router. Then, depending on your requirements, connect standard telephones, fax machines, phone lines and/or a PBX system to the Max. Users will be calling from regular phones, so they won't have to learn a complicated new phone system.

Additional Business Management Tools

The Max 430 also features:

- IVR (Interactive Voice Response) functionality, enabling call connection and account balance announcements, password protection and various user greetings
- The capacity to make PSTN calls through the FXO port
- The ability to dial other extensions connected to the unit, which can be especially beneficial in an office environment
- Compatibility with the Max ABS (Automated Billing System) software, allowing you to set your own rates, generate detailed bills and view call detail records



Requirements

- Switch or router
- 17 Kbps per call
- Standard telephones, fax machines, phone lines and/or a PBX system
- A PC or Mac (for initial configuration and management only)



Max 430