



- Drastically reduce corporate phone bills for calls throughout the world
- Save even more by calling from one Max device to another
- Platform provides a gateway to a host of value-added telephony services
- Supports an office of 100 users (based on calling patterns) by accepting up to 16 analog phones or a PBX system
- Seamlessly interfaces with an analog PBX and is transparent to end-user
- Easily connects to an existing corporate LAN



Max 8/16™

8 port upgrade for a total of 16 ports

Net2Phone® Part # 408-7701

Net2Phone® Part # 408-7708



Now multiple users can make phone calls over Net2Phone's global network...with quality and clarity better than standard IP telephony! Simply connect analog phones or an analog PBX—and save on calls throughout the world!

Voice Quality You Expect At Rates You Don't

The Max 8/16 allows you to make inexpensive telephone calls throughout the world. As these calls are routed over Net2Phone's managed IP network and bypass much of the traditional phone network, you can now receive incredibly low rates with the quality calling experience you expect.

Lower Communication Costs for the Small to Medium Sized Business

Benefit from our tremendously reduced rates on calls throughout the world. Even greater savings are realized for calls from one Max to another, making it the perfect solution for satellite offices or locations you frequently call. In addition, the suite of available telephony services will only increase the efficiency of your business.

Seamless Integration into Any Office Environment

The Max seamlessly integrates with your existing LAN and phone system. Simply connect the Max to your LAN through the 10 Base T Ethernet port. With the FXS version, you can easily connect multiple analog phones or PBX trunk lines in order to make cost-saving calls. The FXO version connects directly to an analog PBX, offering additional functionality such as inbound PSTN calling. With this simple integration, the Max is transparent to all of the users in your office.

Expand the Max as your Business Grows

The Max 8/16 enables eight simultaneous phone calls over the Internet. To meet the demands of a higher calling environment or expanding business, the Max can be upgraded to 16 total ports.

Specifications

Minimum Requirements

- 17 Kbps Internet throughput per line
- Operating System independent (Web-based setup and management)
- PC with Ethernet card (required for initial installation)
- Static or dynamic IP address

LAN Connection

- 10BaseT interface (half/duplex)
- RJ-45 connection

Analog Telephone Interface

- Number of Channels: 8 (upgradeable to 16)
- Analog Voice Interface: FXS or FXO, RJ-48, 8/16 ports

Control Interface

- RS-232C DB-9, 1 port asynchronous serial communication at 19200bps

General

- Physical: 53.5 x 439 x 300 mm
- Power: 110-220 VAC, 1 A (max.), 50/60 Hz, 60 W (max.)



Copyright 2001, Net2Phone, Inc. Net2Phone is a registered trademark of Net2Phone, Inc. Net2Phone Max and IP Phone are trademarks of Net2Phone, Inc. Specifications, pricing, and rates are subject to change without notice.

Net2Phone, Inc. • 520 Broad Street • Newark, NJ • 07102
www.net2phone.com/max

Max 8/16™