

Linksys SPA941

The Linksys SPA941 IP phone enables VoiceDirector customers to place low-cost calls all over the world

VoiceDirector Compatible

The Linksys SPA941 provides corporate customers with a multiple line VoIP calling solution. This IP phone can be easily implemented at any location on the VoiceDirector network, enabling employees to make low-cost calls from headquarters and home/satellite offices.

Corporate Calling Features

The Linksys SPA941 delivers a complete set of business class calling features, including:

- Speakerphone
- Caller waiting
- Call blocking (anonymous and selective)
- Caller ID name and number (plus outbound Caller ID blocking)
- Do not disturb
- Subsequent incoming calls with calling name and number
- Multiple ring tones with selectable ring tone per line



Linksys SPA941 Specifications

Hardware Specifications

Network Interface	One 10/100 Base-T Ethernet port for WAN interface
LED Indicators	Four call appearance/line buttons with associated tri-color LED, line LED state indication (active, idle, on hold, unregistered), speakerphone on/off button with LED, headset on/off button with LED, mute button with LED, message waiting indicator with LED, voicemail message retrieval button, hold button, LED test function
Adapter	12-Volt DC adaptor

Standards

Speech Codec Capabilities	G.711 (A-law and u-law), G.726 (16/24/32/40 Kbps), G.729a, G.723.1 (6.3 kbps, 5.3 kbps)
Regulatory Approvals	FCC (Part 15, Class B), CE, A-Tick, ICES-003

Physical Specifications

Dimensions (H x W x D)	6.3" x 7.68" x 7.09"
Operational Temperature	41° to 113° F (5° to 45° C)
Storage Temperature	-13° to 185° F (-25° to 85° C)
Humidity	10% to 90% (non-condensing)

For more information, please visit www.voicedirector.net